

LED A1 Troffer

- Auto sensing 100 - 277VAC for ease of installation.
- 100-277VAC Class 2 externally mounted power supply, 0-10VDC Dimming PS optional
- Non directional - homogeneous illumination
- Fast and simple installation for retrofit or new construction
- Patent licensed program protected
- 10 yr. warranty



Technical Specifications

Model:	LED-A1-22	LED-A1-24
Nominal Watts:	32W	50W
Nominal Lumens:	3520lm	5000lm
Lm/W:	≥110	≥100
Voltage:	100 - 277VAC	
Available CCT:	3500K / 4000K / 5000K	
Beam Angle:	140°	
CRI:	≥83	
Power Factor:	≥.99	
Control Options:	0-10VDC / Programmable IR Occupancy - Daylight	
Optional Emergency Power Pack:	90 min. @ 10W / 500ma	
L70 Lifespan:	≥72,000 hrs.	
Operating Temp:	-30°C - +40°C	
Compliance:	DLC / UL / cUL / RoHS	
Warranty:	10 Yr. Limited Warranty	
Max. Outside Dimensions (in):	23.7 x 23.7 x 3.95in	23.7 x 47.7 x 3.95in

Notes: All values nominal.

PART NUMBER SPECIFICATION						
	-	-	-	- 100277	-	
Series	Model	Wattage	CCT	Voltage:	Control	Emergency Pack
A1 Series	22 (2 x 2 Troffer)	32 - (32W A1 Series)	35 (3500K) 40 (4000K) 50 (5000K)	100277 (100-277VAC)	D (Dimming) SM(Sensor Module)	Blank (Not included) EMP - Emergency Pack Included
	24 (2 x 4 Troffer)	50 - (50W A1 Series)				

