

Ballast Compatible LED T5 Tube

- High efficiency (up to 115 Lm/W) retrofit for T5 lamps in residential, commercial and industrial applications
- Economical price for faster ROI in any scale of retrofit project type
- 100-277VAC Class 2 externally mounted power supply, 0-10VDC Dimming PS optional
- Internal Driver for easy installation using existing AC powered lamps
- Patent licensed program protected
- 10 Year limited warranty



Technical Specifications

Model:	T54 - 25W	T54 - 28
Wattage @ 120VAC:	25	28
Lumen/Watt:	112	114
Rated Lumens @ 3000K:	2600	3000
Rated Lumens @ 5000K:	2800	3200
CRI:	85	85
THD @ 120VAC:	9.9	7.79
Ballast Compatibility:	UL Type A - Electronic Ballast Compatible (See Mfr. Approved Ballast List)	
Lamp Base:	G5 Bi-pin	
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K	
L70 Lifespan:	50,000 Hrs.	
Beam Angle / Field Angle	120° / 160°	
Length / Diameter:	47.165in / .629in (16mm)	
Weight:	.41lbs / 190g	
Operation Temperature:	10°C to +40°C Ambient	
Limited Warranty:	10 Years	

Notes: Tested Values@Ta=25°C All values are nominal.

PART NUMBER SPECIFICATION

Series	Length / Series	Nominal Wattage	CCT Option
BC - T5	T54 - (4ft)	25 (25 Watts) 28 (28 Watts)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K)

