

Parking / Gas Station / Canopy Series

- High efficiency (115 Lm/W) retrofit for Parking, Gas Station, Canopy Applications
- Economical price for faster ROI in any scale of retrofit project type
- 100-277VAC Class 2 externally mounted power supply, 0-10VDC Dimming PS optional
- Patent licensed program protected
- 10 Year limited warranty



Technical Specifications

| | | |
|------------------------|---|----------|
| Model: | PGC - 45 | PGC - 70 |
| Nominal Watts: | 45W | 70W |
| Nominal Lumens: | 4050lm | 5900lm |
| Lm/W: | ≥90 | |
| Voltage: | 100 - 277VAC (Standard) 100 - 382VAC (Optional) | |
| Available CCT: | 4000K / 5000K | |
| Optics: | IES Type 5 | |
| CRI: | ≥72 | |
| Power Factor: | ≥.90 | |
| Dimming Option: | 0-10VDC | |
| Control Sensor Option: | Dual Photo / Motion Programmable Step Dim | |
| L70 Lifespan: | ≥50,000 hrs. | |
| Operating Temp: | -25°C - +40°C | |
| Ingress Protection: | UL Damp Location Rated | |
| Compliance: | DLC / UL / cUL / RoHS | |
| Warranty: | 10 Yr. Limited Warranty | |
| Dimensions (in): | 9.57 x 9.57 x 3.07 | |

Notes: All values nominal. See Data Sheet for measured LM79 values.

| PART NUMBER SPECIFICATION | | | Part Number Example: FF-22-A8-30-30-100277-D | | |
|---------------------------|--------------|--------------------------|--|---------------------------------|---------------------------------------|
| Series | Model | CCT | Voltage: | Dimming | Sensor Control |
| PGC Series | 45 (45 Watt) | 40 (4000K) 50 (5000K) | 100277 (100-277VAC) 100382 (100-382VAC) | D (Dimming) ND (Non Dimming) | NC - No Control SM - Sensor Module |
| | 70 (70 Watt) | | 100277 (100-277VAC) | | |

