

LED A2 Troffer

- Auto sensing 100 - 277VAC for ease of installation.
- 100-277VAC Class 2 externally mounted power supply, 0-10VDC Dimming PS optional
- Non directional - homogeneous illumination
- Fast and simple installation for retrofit or new construction
- Patent licensed program protected
- 10 yr. warranty



Technical Specifications

Model:	A2 - 22 - 27	A2 - 22 - 40	A2 - 24 - 52	A2 - 24 - 65
Lumens (@4000K):	4200	5300	5150	6200
Power Consumption:	27W	40W	52W	65W
Frame Dimensions W/D/H	23.8in x 23.8in x 3.9in / 605mm x 605mm x 100mm		23.8in x 46.9in x 3.9in / 605mm x 1212mm x 100mm	
Dimming (Standard):	0-10VDC			
Voltage:	Power Supply 100-277 VAC			
CRI:	≥80			
CCT Options:	3000K / 4000K / 5000K			
Operating Temperature:	-20° C - +70° C			
Protection Class:	UL Damp Location			
L70 Rated Lifespan:	>50,000hrs.			
Limited Warranty:	10 yrs.			

Notes: Wattage +/- 10% CCT Values +/- 200K Lumen Values +/- 250Lms. CRI +/- 5%

PART NUMBER SPECIFICATION

	-	-	-	- 010	- 100277
Model	Size - Series	Wattage Option	CCT Option	Dimming	Voltage
	22 - (2 x 2ft)	22 (22W) 40 (40W)	30 (3000K) 40 (4000K) 50 (5000K)	010 (Standard 0-10VDC)	100277 (100 - 277VAC)
	24 - (2 x 4ft)	52 (52W) 65 (65W)			

